

## Hellhound AMD Radeon™ RX 7700 XT 12GB GDDR6


### SPECIFICATION

EAN CODE	4713436174950	Bus Standard	PCIE 4.0
Graphics Engine	RX7700XT 12G-L/OC	Display Connectors	1 x HDMI 2.1 , 3 x DisplayPort 2.1
Video Memory	12GB GDDR6	Form Factor	ATX
Stream Processor	3456 Units	Cooler	2.5 Slot Triple Fan
Engine Clock	Game 2276 MHz(OC)/ 2226 MHz(Silent)	Power Connector	Two 8-pin PCI Express Power Connector
	Boost 2599 MHz(OC)/ 2584 MHz(Silent)	OpenGL	4.6
Memory Clock	18.0 Gbps	DirectX® Support	12
Memory Interface	192-bit	Minimum System Power	750W
		Card Dimension(mm)	322*134*50mm 332*147*50mm(w/bracket)

### Accessories Bundle


\* 'Game Clock' is the expected GPU clock when running typical gaming applications, set to typical TGP (Total Graphics Power). Actual individual game clock results may vary.  
\* 'Boost Clock' is the maximum frequency achievable on the GPU running a bursty workload. Boost clock achievability, frequency, and sustainability will vary based on several factors, including but not limited to: thermal conditions and variation in applications and workloads.

### FEATURES



#### Dual BIOS

Choosing the BIOS that fits your need: better overclocking or silent operation.



#### GPU Direct-Contact Copper Plate

A large copper plate provides direct contact with the GPU while covering VRAM area to increase the heat transfer threshold to the max.




#### Brand New Amethyst LED color

A brand new amethyst purple LED lighting is added to the product while the original ice blue is also retained.



#### Intelligent Fan Controller

Utilizing temperature detection from a smart chip, fans will start running when the GPU reaches 60°C and shut down below 50°C.



#### Back Plate

The metal back plate is extremely rigid to strengthen the card to prevent PCB bending.



#### Triple Ring-Fan

The 2X 100mm and 1X 90mm Ring-fan design improves the cooling performance.